

100486

MSDS Report

Applicant's name	SHENZHEN LIDEA BATTERY CO., LTD.				
Applicant's Address	3/F, NO.5 Bldg, Houhai Xufa Tech Park, Loucun, GongMing Town Guangming New District, Shenzhen, China.				
Name of Sample	LI-ION RECHARGEABLE BATTERY				
Model	LIR2032				
Nominal Voltage	3.6V		7		
Rated Capacity	40mAh, 0.144W	h			
Weight	2.8g				
Size (D×T)	(20.0×3.2)mm				
,	Shenzhen TCT	Testing Technolog	gy Co., Ltd.		
Prepared By	1B/F., Building District, Shenzhe	1, Yibaolai Indi en, Guangdong, (ustrial Park, (China.	Qiaotou,	Fuyong, Baoan
Report No.	TCT191212M11	0			

Written by: Summer Yang Approved by:____

Inspected by: Army Zeng

Date:





Section 1- Chemic	al Product & Company Id	dentification	
Name of Sample	LI-ION RECHARGEABLE BATT	ERY	
Manufacturer's name	SHENZHEN LIDEA BATTERY C	O., LTD.	
Manufacturer's Address	3/F, NO.5 Bldg, Houhai Xufa Tec New District, Shenzhen, China.	h Park, Loucun, GongMi	ng Town Guangming
Contact Person	Mr. Yi		
Tel	+86-755-27863350		
Fax	+86-0755-25179976		<u> </u>
Emergency Tel	+86-755-27863350		
E-mail	515173348@qq.com		

Section 2- Hazards Identification				
Classification of Danger	See section 14.			
Primary Route(s) of Exposure	Eye, skin contact, ingestion.			
Health Hazard	The batteries are not hazardous manufacturer under normal confire, heat, leakage of internal corincluding but not limited to the forcircuited, put into fire, whacked crushed, and broken.	ditions. In case of abuse, there mponents, which could cause of collowing cases: charged for lor	e's Hazard of rupture, casualty loss. Abuses ng time, short	

Report No.: TCT191212M110

91212M110 Page 2 of 8



Section 3- Composition/In	formation on Ingredie	ents
Chemical Name	Concentration or concentration ranges ((%) CAS Number
Lithium Cobalt Oxide	15-40	12190-79-3
Graphite	10-30	7782-42-5
Phosphate(1-), hexafluoro-, lithium	10-30	21324-40-3
Copper	7-13	7440-50-8
Aluminum foil	5-10	7429-90-5
Nickel	1-5	7440-02-0

Labeling according to EC directives.

No symbol and Hazard phrase are required.

Note: CAS number is Chemical Abstract Service Registry Number.

N/A=Not apply.

Section 4- First A	Aid Measures
Eye	Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.
Skin	Remove contaminated clothes and rinse skin with plenty of water or shower for 15 minutes. Get medical aid.
Inhalation	Remove from exposure and move to fresh air immediately. Use oxygen if available.
Ingestion	Give at least 2 glasses of milk or water. Induce vomiting unless patient is unconscious. Call a physician.

Section 5- Fire Fighting Measures			
Characteristics of Hazard	Dusts at sufficient concer generates toxic fumes.	ntrations can form explosive mix	tures with air. Combustion
Hazardous Combustion Products	Carbon dioxide.		
Fire-extinguishing Methods and Extinguishing Media	For small fires, use water	spray, dry chemical, carbon dio	xide or chemical foam.

Report No.: TCT191212M110





Attention in Fire-extinguishing

Wear self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6- Accidental Release Measures			
Personal Precautions, protective equipment, and emergency procedure	es .	In case of rupture. Attention! Corrosive material. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Refer to protective measures listed in Sections 7 and 8.	
Environmental Precautions		Prevent product from contaminating soil and from entering sewers or waterways.	
Methods and materials for Containmen	nt	Stop the leak if safe to do so. Contain the spilled liquid with dry sand or earth. Clean up spills immediately.	
Methods and materials for cleaning up		Absorb spilled material with an inert absorbent (dry sand or earth). Scoop contaminated absorbent into an acceptable waste container. Collect all contaminated absorbent and dispose of according to directions in Section 13. Scrub the area with detergent and water; collect all contaminated wash water for proper disposal.	

Section 7- Handling and Storage	
Handling	The battery may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.
Storage	Store in a cool, dry, well-ventilated area away from incompatible substances. Store locked up. Keep out of the reach of children.
Other Precautions	In case of rupture. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Use personal protection equipment.

Section 8 - Exposure Controls/Persona	al Protection
Engineering Controls	Use adequate ventilation to keep airborne concentrations low. If used under conditions that generate particulates, the ACGIH TLV-TWA of 3mg/m³ respirable fraction (10mg/m³ total) should be observed.

Report No.: TCT191212M110



Personal Protective Equips

Eye and Face Protection: None required for consumer use. If there is a Hazard of contact: Tight sealing safety goggles. Face protection shield.

Skin and Body Protection: None required for consumer use. If there is a Hazard of contact: Wear protective gloves and protective clothing.

Respiratory Protection: No protective equipment is

Respiratory Protection: No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Section 9- Phy	sical and Chemical Properties			
	Appearance: Cylindrical			
Physical State	Color: Silver			
	Odour: If leaking, smells of medical ether.		14	
Change in condit	ion			
рН	Not applicable as supplied.			Š
Flash Point	Not applicable unless individual component	s exposed.	***************************************	
Flammability	Not applicable unless individual component	s exposed.		
Relative density:	Not applicable unless individual component	s exposed.		
Solubility (water)	Not applicable unless individual component	s exposed.		
Solubility (other)	Not applicable unless individual component	s exposed.		

Section 10 – Stability and Reactivity	
Chemical Stability	Stable under recommended storage conditions.
Possibility of Hazardous Reactions	None under normal processing.
Conditions to Avoid	Exposure to air or moisture over prolonged periods.
Incompatible materials	Acids, Oxidizing agents, Bases.
Hazardous Decomposition Products	Carbon oxides.

Report No.: TCT191212M110

Hotling: 400 6611 140 Tol: 96 755 27672220 Equ. 96 755 27672220 Ethilling: 410



Section 11 – Toxicological Informatio	n
Irritation	In the event of exposure to internal contents, vapour fumes may be very irritating to the eyes and skin.
Sensitization	Not Available
Reproductive Toxicity	Not Available.
Toxicologically Synergistic Materials	Not Available.

Section 12-Ecological Information	
General note:	Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Anticipated behavior of a chemical product in environment/possible environmental impact/ ecotoxicity	Not Available.

Section 13 – Disposal Considerations		
Waste Treatment	Recycle or dispose of in accordance with government, state & local regulations.	
Attention for Waste Treatment	Deserted batteries shouldn't be treated as ordinary trash. Shouldn't be thrown into fire or placed in high temperature. Shouldn't be dissected, pierced, crushed or treated similarly. Best disposal method is recycling.	

Section 14 – Transport Information		
UN number	3480	
Proper shipping name	Lithium ion batteries (limited to a maximum of 30% SoC)	
Label(s) / Placard Required	Miscellaneous Lithium batt	
Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises		
ICAO / IATA:	Can be shipped by air in accordance with International Civil Aviation Organization (ICAO), TI or International Air Transport Association (IATA), DGR Packing Instructions (PI) 965 Section II appropriate of IATA DGR 61 st (2020 Edition) for transportation.	

Report No.: TCT191212M110

Page 6 of 8 Hatting: 400 6611 140 Tal- 96 755 27672220 Equ. 96 755 27672220



IMDG CODE:	The batteries are not restricted to IMDG Code 2018 Edition (Amdt 39-18) according to special provision 188.
DOT:	Other requirements for the US Department of Transportation (DOT) Subchapter C, Hazardous Materials Regulations if shipped in compliance with 49 CFR 173.185.
ADR/ ADN:	The batteries are not subject to the provisions of United Nations Economic Commission for Europe (UNECE) ADR/ADN if they meet the requirements of special provision 188 of Chapter 3.3. Applicable as from 1 January 2019.

In addition, to be permitted in transport each lithium cell and battery types must have passed the applicable tests set out in Subsection 38.3 of the UN Manual of Tests and Criteria.

Section 15 - Regulatory Information

Dangerous Goods Regulations

Recommendations on the Transport of Dangerous Goods-Model Regulations (20th revised edition)

Recommendations on the Transport of Dangerous Goods-Manual of Tests and Criteria

International Air Transport Association (IATA)

International Maritime Dangerous Goods (IMDG Code 2018 Edition Amdt 39-18)

Technical Instructions for the Safe Transport of Dangerous Goods

Classification and code of dangerous goods (GB 6944-2012)

2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Toxic Substance Control Act (TSCA)

Code of Federal Regulations

In accordance with all Federal, State and local laws

Report No.: TCT191212M110


Hotling: 400 6611 140 Tol: 86 755 27672220 Earl 96 755 27672222 http://www.tal.it.




Section 16 – Additional Information

MSDS creation date: 2020 Version: 1.0

Sample photo:





To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

The data/information contained herein has been reviewed and approved for general release on the basis that this document contains no export controlled information.

******End of report*****

Shenzhen TCT Testing Technology Co., Ltd.

1B/F., Building 1, Yibaolai Industrial Park, Qiaotou, Fuyong, Baoan District, Shenzhen, Guangdong, China Report Search Number: TCT191212M110

Search System: http://www.tct-lab.com