

18-6528



SAFETY DATA SHEET

Revision Date 03-Oct-2018

Version 10

1. IDENTIFICATION

Product identifier

Product Name PX FORM-A-GASKET SEALANT #2 11 OZ.

Other means of identification

Product Code 80011

Recommended use of the chemical and restrictions on use

Recommended Use Sealant
Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

ITW Permatex
6875 Parkland Blvd.
Solon, OH 44139 USA

May Also Be Distributed by:

ITW Permatex Canada
101-2360 Bristol Circle
Oakville, ON Canada L6H 6M5
Telephone: (800) 924-6994

24-hour emergency phone number

Chem-Tel: 800-255-3924
International Emergency:
00+1+ 813-248-0585
Contract Number: MIS0003453

E-mail address: mail@permatex.com

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization	Category 1
Carcinogenicity	Category 2


Label elements

Emergency Overview

Signal word

Warning

May cause an allergic skin reaction
Suspected of causing cancer



Appearance Black

Physical state Paste

Odor Alcohol

Precautionary Statements - Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Contaminated work clothing should not be allowed out of the workplace

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
 IF ON SKIN: Wash with plenty of soap and water
 If skin irritation or rash occurs: Get medical advice/attention
 Wash contaminated clothing before reuse

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

- Not applicable

Unknown acute toxicity

16.79 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance(s)

Chemical Name	CAS No	Weight-%
FUMARATED RESIN	65997-04-8	10 - 30
ETHANOL	64-17-5	5 - 10
2-PROPANOL	67-63-0	1 - 5
METHANOL	67-56-1	0.1 - 1
METHYL ISOBUTYL KETONE	108-10-1	0.1 - 1

4. FIRST AID MEASURES

Description of first aid measures

General advice	Get medical advice/attention if you feel unwell.
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Skin contact	IF ON SKIN: Wash skin with soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Inhalation	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.
Ingestion	IF SWALLOWED: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

Most important symptoms and effects, both acute and delayed

Symptoms May cause allergic skin reaction.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO₂), Dry chemical, Foam

Unsuitable extinguishing media

None

Specific hazards arising from the chemical

None in particular.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin. Use personal protective equipment as required.

Environmental precautions

Environmental precautions See section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.

Conditions for safe storage, including any incompatibilities

Storage Conditions Store in a well-ventilated place. Keep cool.

Incompatible materials Strong oxidizing agents

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
ETHANOL 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1900 mg/m ³	IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m ³
2-PROPANOL 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m ³	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m ³ STEL: 500 ppm STEL: 1225 mg/m ³
METHANOL 67-56-1	STEL: 250 ppm TWA: 200 ppm S*	TWA: 200 ppm TWA: 260 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m ³ (vacated) S*	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m ³ STEL: 250 ppm STEL: 325 mg/m ³
METHYL ISOBUTYL KETONE 108-10-1	STEL: 75 ppm TWA: 20 ppm	TWA: 100 ppm TWA: 410 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 205 mg/m ³ (vacated) STEL: 75 ppm (vacated) STEL: 300 mg/m ³	IDLH: 500 ppm TWA: 50 ppm TWA: 205 mg/m ³ STEL: 75 ppm STEL: 300 mg/m ³

NIOSH IDLH *Immediately Dangerous to Life or Health*

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

Respiratory protection Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Paste
Appearance Black
Odor Alcohol
Odor threshold No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting point / freezing point	No information available	
Boiling point / boiling range	82 °C / 180 °F	
Flash point	Does not apply	ASTM D 4359
Evaporation rate	7.7	Ether = 1
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	No information available	
Lower flammability limit:	No information available	
Vapor pressure	33 mm Hg @ 68°F	
Vapor density	2.0	Air = 1
Relative density	1.5	
Water solubility	Partially soluble	
Solubility in other solvents	No information available	
Partition coefficient	No information available	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	

Other Information

Softening point	No information available
Molecular weight	No information available
VOC Content (%)	11%
Density	No information available
Bulk density	No information available

10. STABILITY AND REACTIVITY

Reactivity

Stable under normal conditions

Chemical stability

Stable under recommended storage conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Excessive heat.

Incompatible materials

Strong oxidizing agents

Hazardous Decomposition Products

Carbon oxides
Aldehydes
Carboxylic acids

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation	May cause irritation of respiratory tract.
Eye contact	Contact with eyes may cause irritation. May cause redness and tearing of the eyes.
Skin contact	May cause skin irritation and/or dermatitis. Repeated or prolonged skin contact may cause

allergic reactions with susceptible persons.

Ingestion

Ingestion may cause irritation to mucous membranes.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
ETHANOL 64-17-5	= 7060 mg/kg (Rat)	-	= 124.7 mg/L (Rat) 4 h
2-PROPANOL 67-63-0	5050 mg/kg	12800 mg/kg	= 72600 mg/m ³ (Rat) 4 h
METHANOL 67-56-1	= 6200 mg/kg (Rat)	= 15800 mg/kg (Rabbit)	= 22500 ppm (Rat) 8 h = 64000 ppm (Rat) 4 h
METHYL ISOBUTYL KETONE 108-10-1	= 2080 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	= 8.2 mg/L (Rat) 4 h

Information on toxicological effects**Symptoms**

No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Sensitization**

No information available.

Germ cell mutagenicity

No information available.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
ETHANOL 64-17-5	A3	-	Known	X
METHYL ISOBUTYL KETONE 108-10-1	A3	Group 2B	-	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Chronic toxicity

May cause adverse effects on the bone marrow and blood-forming system. May cause adverse liver effects.

Target Organ Effects

Blood, Central nervous system, Eyes, Liver, Reproductive System, Respiratory system, Skin, Thyroid, Lungs.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	9865 mg/kg
ATEmix (dermal)	48276 mg/kg
ATEmix (inhalation-dust/mist)	85.1 mg/l

12. ECOLOGICAL INFORMATION**Ecotoxicity**

18.075 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Chemical Name	Partition coefficient
---------------	-----------------------

ETHANOL 64-17-5	-0.32
2-PROPANOL 67-63-0	0.05
METHANOL 67-56-1	-0.77
METHYL ISOBUTYL KETONE 108-10-1	1.19

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number Not applicable

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
ETHANOL 64-17-5	Toxic Ignitable
2-PROPANOL 67-63-0	Toxic Ignitable
METHANOL 67-56-1	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT
Proper shipping name: Not regulated

IATA
Proper shipping name: Not regulated

IMDG
Proper shipping name: Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
 DSL/NDSL Complies
 EINECS/ELINCS Complies
 ENCS Not determined
 IECS Complies
 KECL Complies
 PICCS Complies
 AICS Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
 EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances
 IECSC - China Inventory of Existing Chemical Substances
 KECL - Korean Existing and Evaluated Chemical Substances
 PICCS - Philippines Inventory of Chemicals and Chemical Substances
 AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
2-PROPANOL - 67-63-0	1.0

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
METHANOL 67-56-1	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
METHYL ISOBUTYL KETONE 108-10-1	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
ETHANOL - 64-17-5	Carcinogen Developmental
CRYSTALLINE SILICA - 14808-60-7	*Carcinogen
TITANIUM DIOXIDE - 13463-67-7	*Carcinogen (airborne, unbound particles of respirable size)
METHANOL - 67-56-1	Developmental
CARBON BLACK - 1333-86-4	*Carcinogen (airborne, unbound particles of respirable size)
METHYL ISOBUTYL KETONE - 108-10-1	Carcinogen Developmental

- *The asterisked chemical(s) listed are not subject to Proposition 65 because they are not airborne in the finished product
- Ethanol has been shown to be carcinogenic in long-term studies only when consumed as alcoholic beverage
- Ethanol has been shown to be a reproductive toxin only when consumed as an alcoholic beverage

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
KAOLIN 1332-58-7	X	X	X
ETHANOL 64-17-5	X	X	X
2-PROPANOL 67-63-0	X	X	X
CRYSTALLINE SILICA 14808-60-7	X	X	X

TITANIUM DIOXIDE 13463-67-7	X	X	X
METHANOL 67-56-1	X	X	X
CARBON BLACK 1333-86-4	X	X	X
METHYL ISOBUTYL KETONE 108-10-1	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

D2B - Toxic materials

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

<u>NFPA</u>	Health hazards 2	Flammability 1	Instability 0	-
<u>HMIS</u>	Health hazards 2	Flammability 1	Physical hazards 0	Personal protection B

NFPA (National Fire Protection Association)
HMIS (Hazardous Material Information System)

Revision Date 03-Oct-2018

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet