282862

Product Number 840

Issuing Date No data available

Revision Date 03-11-2015

Revision Number 2

SAFETY DATA SHEET



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier	
Product Name	Acetone
Other means of identification	
Synonyms	None
Recommended use of the chemical	and restrictions on use
Recommended Use	Multi-purpose solvent
Uses advised against	No information available
Details of the supplier of the safety	data sheet
Supplier Name Supplier Address	Sunnyside Corporation 225 Carpenter Avenue Wheeling IL 60090 US Depe:8002238611
Supplier Phone Number	Phone:8003238611 Fax:8475419043
Supplier Email Emergency telephone number	sscontact@sunnysidecorp.com Chem Trec 8004249300

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Flammable liquids	Category 2

GHS Label elements, including precautionary statements



Signal word	Emergency Overvie Danger	···
Hazard Statements Causes serious eye irritation May cause drowsiness or dizziness Highly flammable liquid and vapor		
Appearance Clear	Physical State Liqui	id Odor Pungen

Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area Keep away from heat/sparks/open flames/hot surfaces. - No smoking Keep container tightly closed Ground/bond container and receiving equipment Use explosion-proof electrical/ ventilating/ lighting/ equipment Use only non-sparking tools Take precautionary measures against static discharge Wear protective gloves/protective clothing/eye protection/face protection

Keep cool

Precautionary Statements - Response

Skin

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a POISON CENTER or doctor/physician if you feel unwell

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity



Other information

May be harmful if inhaled PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%	Trade Secret
Acetone	67-64-1	60 - 100	*

The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES		
First aid measures		
General Advice	Show this safety data sheet to the doctor in attendance.	
Eye Contact	If symptoms persist, call a physician. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area.	
Skin Contact	In the case of skin irritation or allergic reactions see a physician. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.	
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, (trained personnel should) give oxygen.	
Ingestion	Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician.	
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.	
Most important symptoms and e	effects, both acute and delayed	
Most Important Symptoms and Effects	Burning sensation. Drowsiness. Dizziness.	
Indication of any immediate medical attention and special treatment needed		
	—	

Treat symptomatically.



Notes to Physician

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

Unsuitable Extinguishing Media

CAUTION: All these products have a very low flash point. Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

Vapors can form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard.

Uniform Fire Code	Flammable Liquid: I-B
	Irritant: Liquid

Hazardous Combustion Products Carbon oxides.

Explosion Data Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge Yes.

Protective equipment and precautions for firefighters Move containers from fire area if you can do it without risk.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions	ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Stop leak if you can do it without risk.
Other Information	Water spray may reduce vapor; but may not prevent ignition in closed spaces.
Environmental Precautions	
Environmental Precautions	Prevent entry into waterways, sewers, basements or confined areas.
Methods and material for containm	ent and cleaning up
Methods for Containment	A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.
Methods for cleaning up	Use clean non-sparking tools to collect absorbed material. Soak up with inert absorbent material. Dike far ahead of liquid spill for later disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Conditions for safe storage, includi	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat/sparks/open flames/hot surfaces No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions.
Storage	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials.
Incompatible Products	Keep in an area equipped with sprinklers. None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone	STEL = 750 ppm	TWA: 1000 ppm	IDLH: 2500 ppm 10% LEL
67-64-1	TWA: 500 ppm	TWA: 2400 mg/m ³	TWA: 250 ppm
		(vacated) TWA: 1800 mg/m ³	TWA: 590 mg/m ³
		(vacated) TWA: 750 ppm	
		(vacated) STEL: 1000 ppm	
		(vacated) STEL: 2400 mg/m ³	

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls

Engineering Measures Showers Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection	Tight sealing safety goggles.
Skin and Body Protection	Long sleeved clothing. Chemical resistant apron. Impervious gloves. Antistatic boots.
Respiratory Protection	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical State Appearance Color
Property pH Melting / freezing point Boiling point / boiling range Flash Point Evaporation Rate Flammability (solid, gas) Flammability Limit in Air Upper flammability limit Lower flammability limit Vapor pressure Vapor density Specific Gravity Water Solubility Solubility in other solvents Partition coefficient: n-octanol/wat Autoignition temperature Decomposition temperature Kinematic viscosity Dynamic viscosity Explosive properties Oxidizing Properties
Ovidizing Froperices

Other Information

Softening Point VOC Content (%) Particle Size Particle Size Distribution

Values N/A No data available 56 °C / 133 °F -18 C / 0 F No data available N/A No data available 2.5% @ 77 °F 213 mmHg @ 75 °F No data available No data available Soluble in water No data available terNo data available 869 °F No data available No data available No data available No data available No data available

Liquid Clear

Colorless

No data available Exempt No data available Odor Odor Threshold Pungent No information available

Remarks/ Method

None known None known None known None known None known

None known None known None known None known None known None known None known None known

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Caustics, amines, alkanolamines, ammonia, strong oxidizing agents and chlorinated compounds.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation	Specific test data for the substance or mixture is not available. May cause drownsiness and dizziness based on components. May cause irritation of respiratory tract.
Eye Contact	Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. May cause redness, itching, and pain. May cause temporary eye irritation.
Skin Contact	Specific test data for the substance or mixture is not available. May cause irritation. Prolonged contact may cause redness and irritation.
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone	-	-	= 50100 mg/m ³ (Rat) 8 h
67-64-1			- · · · /

Information on toxicological effects

Symptoms

May cause redness and tearing of the eyes.

Delayed and immediate effects as well as chronic effects from short and long-term exposure



Sensitization	No information available.
Mutagenic Effects	No information available.
Carcinogenicity	Contains no ingredient listed as a carcinogen.
Reproductive Toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Chronic Toxicity	No known effect based on information supplied.
Target Organ Effects	Eyes. Central Nervous System (CNS). Respiratory system. Skin.
Aspiration Hazard	No information available.
Noncontract management of tradition Day	- deset before etter

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (inhalation-dust/mist)

100.20 mg/l

12. ECOLOGICAL INFORMATION

<u>Ecotoxicity</u> The environmental impact of this product has not been fully investigated.

Persistence and Degradability

No information available.

Bioaccumulation

No information available

Chemical Name	Log Pow		
Acetone	-0.24		
67-64-1			

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods	This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).
Contaminated Packaging	Dispose of contents/containers in accordance with local regulations.

US EPA Waste Number D001 U002

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone				U002
67-64-1				

California Hazardous Waste Codes 212

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste		
Acetone 67-64-1	Ignitable		

14. TRANSPORT INFORMATION

DOT

UN-No. Proper Shipping Name Hazard Class Packing Group Description	UN1090 ACETONE 3 II UN1090, ACETONE, 3, II
<u>TDG</u> UN-No. Proper Shipping Name Hazard Class Packing Group Description	UN1090 ACETONE 3 II UN1090, ACETONE, 3, II
MEX_ UN-No. Proper Shipping Name Hazard Class Packing Group Description	UN1090 ACETONE 3 II UN1090 ACETONE, 3, II
ICAO UN-No. Proper Shipping Name Hazard Class Packing Group Description	UN1090 ACETONE 3 II UN1090, ACETONE, 3, II
<u>IATA</u> UN-No. Proper Shipping Name Hazard Class	UN1090 ACETONE 3

Packing Group Description	II UN1090, ACETONE, 3, II
IMDG/IMO UN-No. Proper Shipping Name Hazard Class Packing Group EmS No. Description	UN1090 ACETONE 3 II F-E, S-D UN1090, ACETONE, 3, II, FP -18C
<u>RID</u> UN-No. Proper Shipping Name Hazard Class Packing Group Classification code Description	UN1090 ACETONE 3 II F1 UN1090 ACETONE, 3, II
ADR UN-No. Proper Shipping Name Hazard Class Packing Group Classification code Description	UN1090 ACETONE 3 II F1 UN1090 ACETONE, 3, II
ADN UN-No. Proper Shipping Name Hazard Class Packing Group Classification code Description Hazard Labels Limited Quantity Ventilation	UN1090 ACETONE 3 II F1 UN1090 ACETONE, 3, II 3 1 L VE01

15. REGULATORY INFORMATION

International Inventories

TSCA DSL

Complies All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313 Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No



CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

<u>CERCLA</u>

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

	Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
	Acetone	5000 lb		RQ= 2270 kg final RQ
	67-64-1			RQ= 5000 lb final RQ
1	IC Otata Damulatiana			

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Acetone	Х	X	Х	Х	
67-64-1					

International Regulations

Mexico

National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Acetone		Mexico: TWA= 1000 ppm
67-64-1(60 - 100)		Mexico: TWA= 2400 mg/m ³
		Mexico: STEL= 1260 ppm
		Mexico: STEL= 3000 mg/m ³

Mexico - Occupational Exposure Limits - Carcinogens

Canada

WHMIS Hazard Class B2 - Flammable liquid D2B - Toxic materials



16. OTHER INFORMATION

NFPA	Health Hazards 2	Flammability 3	Instability 0	Physical and Chemical Hazards -
HMIS	Health Hazards 2	Flammability 3	Physical Hazard 0	Personal Protection



Prepared By	Product Stewardship 23 British American Blvd. Latham, NY 12110 1-800-572-6501
Revision Date	15-Sep-2014
Revision Note	No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

