



Air Tool Lubricant

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.
Date of issue: 01/05/2016 Revision date: 12/01/2016 Version: 1.0

560319

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : Air Tool Lubricant
Product code : 16-ATL, 128-ATL, 5-ATL & 55-ATL

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Multi-Purpose Lubricant

1.3. Details of the supplier of the safety data sheet

The Blaster Corporation
8500 Sweet Valley Drive
Valley View, Ohio 44125 - USA
T (216) 901-5800 - F (216) 901-5801
www.blastercorp.com

1.4. Emergency telephone number

Emergency number : ChemTel 800-255-3924

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Skin irritation 2
Specific target organ toxicity - Repeated exposure 2
Aspiration toxicity 1

2.2. Label elements

GHS-US labelling

This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations which take precedence over OSHA Hazard Communication labeling. The actual container label will not include the label elements below. The labeling below applies to industrial/professional products.

Hazard pictograms (GHS-US) :



GHS07



GHS08

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : Causes skin irritation. May cause damage to organs through prolonged or repeated exposure
May be fatal if swallowed and enters airways.

Precautionary statements (GHS-US) : Wash hands thoroughly after handling. Wear protective gloves. Do not breathe dust/fume/gas/mist/vapors/spray. Get medical advice/attention if you feel unwell. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
White mineral oil, petroleum	(CAS No) 8042-47-5	60 - 100	Not classified
Distillates, petroleum, hydrotreated middle	(CAS No) 64742-46-7	7 - 13	Flam. Liq. 4 Acute Tox. 4 (Inhalation: dust, mist) Skin Irrit. 2 STOT RE 2 Asp. Tox. 1
Distillates, petroleum, hydrotreated light naphthenic	(CAS No) 64742-53-6	3 - 7	Asp. Tox. 1 Acute Tox. 4 (dust/mist) Carc. 1B

* The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

Air Tool Lubricant

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
First-aid measures after eye contact	: In case of contact, immediately flush eyes with plenty of water. Remove contact lenses, if worn. If irritation persists, get medical attention.
First-aid measures after ingestion	: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: May cause respiratory tract irritation.
Symptoms/injuries after skin contact	: Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.
Symptoms/injuries after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water fog, carbon dioxide, dry chemical or alcohol foam.
Unsuitable extinguishing media	: None known.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Products of combustion may include, and are not limited to: oxides of carbon, hydrocarbons.
-------------	---

5.3. Advice for firefighters

Protection during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.
------------------	--

6.2. Methods and material for containment and cleaning up

For containment	: Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
Methods for cleaning up	: Scoop up material and place in a disposal container. Provide ventilation.

6.3. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/ spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke.
Hygiene measures	: Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Keep out of the reach of children. Keep container tightly closed and in a well-ventilated place. Keep cool.
--------------------	---

7.3. Specific end use(s)

Not available.

Air Tool Lubricant

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

White mineral oil, petroleum(8042-47-5)		
USA ACGIH	ACGIH TWA	Not applicable
USA OSHA	OSHA PEL (TWA)	Not applicable
Distillates, petroleum, hydrotreated middle (64742-46-7)		
USA ACGIH	ACGIH TWA	Not applicable
USA OSHA	OSHA PEL (TWA)	Not applicable
Distillates, petroleum, hydrotreated light naphthenic (64742-53-6)		
USA ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³ (mist)
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³ (mist)

8.2. Exposure controls

Appropriate engineering controls	: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.
Hand protection	: Wear chemically resistant protective gloves.
Eye protection	: Safety glasses or goggles are recommended when using product.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Maintain levels below Community environmental protection thresholds.
Other information	: Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Oily
Colour	: No data available
Odour	: Petroleum
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: < 1
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 371.1 - 460 °C (700 - 860 °F)
Flash point	: > 182.2 °C (>360 °F)
Auto-ignition temperature	: > 315.6 °C (>600 °F)
Decomposition temperature	: No data available
Flammability (solid, gas)	: Notflammable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: > 1 (Air = 1)
Relative density	: 0.86
Solubility	: Insoluble
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: 19 cSt @ 40°C (104°F)
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

Air Tool Lubricant

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal storage conditions.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

Heat. Excessive water.

10.5. Incompatible materials

Strong oxidizing agents. Strong reducing agents.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon, hydrocarbons.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Air Tool Lubricant	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	No data available

White mineral oil, petroleum(8042-47-5)	
LD50 oral rat	>5000 mg/kg
LD50 dermal rabbit	>2000 mg/kg
LC50 inhalation rat	> 5 mg/l/4h

Distillates, petroleum, hydrotreated middle (64742-46-7)	
LD50 oral rat	7400 mg/kg
LD50 dermal rabbit	>2000 mg/kg
LC50 inhalation rat	4.6 mg/l/4h

Distillates, petroleum, hydrotreated light naphthenic (64742-53-6)	
LD50 oral rat	>5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	2.18 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Based on available data, the classification criteria are not met.
Respiratory or skin sensitisation	: Based on available data, the classification criteria are not met.
Germ cell mutagenicity	: Based on available data, the classification criteria are not met.
Carcinogenicity	: Based on available data, the classification criteria are not met.
Reproductive toxicity	: Based on available data, the classification criteria are not met.
Specific target organ toxicity (single exposure)	: Based on available data, the classification criteria are not met.
Specific target organ toxicity (repeated exposure)	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/injuries after inhalation	: May cause respiratory tract irritation.
Symptoms/injuries after skin contact	: Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.
Symptoms/injuries after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

Air Tool Lubricant

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

12.2. Persistence and degradability

Air Tool Lubricant

Persistence and degradability	Not established.
-------------------------------	------------------

12.3. Bioaccumulative potential

Air Tool Lubricant

Bioaccumulative potential	Not established.
---------------------------	------------------

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on ozone layer : No additional information available

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.

SECTION 14: Transport information

In accordance with DOT

14.1. UN number

Not regulated for transport

14.2. UN proper shipping name

Not applicable

14.3. Additional information

Other information : No supplementary information available.

Special transport precautions : Do not handle until all safety precautions have been read and understood.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

15.2. US State regulations

Air Tool Lubricant

State or local regulations	This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.
----------------------------	--

SECTION 16: Other information

Date of issue : 01/05/2016

Revision date : 12/01/2016

Other information : None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.