



355 Hollow Hill Drive
Wauconda, IL 60084

Ph: 847.487.4583
Fax: 847.487.0174

E-mail: sales@surebonder.com
Website: surebonder.com

56-6116

SAFETY DATA SHEET

Prepared to U.S. OSHA, CMA, ANSI, Canadian WHMIS Standards, Australian WorkSafe, Japanese Industrial Standard JIS Z 7250:2000, and European Union standards

1. PRODUCT IDENTIFICATION

TRADE NAME (AS LABELED):
PRODUCT NUMBERS:

Hot Melt Glue
500, 601, 701, 702, 707, 708, 711, 724, 725, 726, 727, 729,
735, 738, 739, 3100, 3120, 3130, 3140, 3145, 3150, 3170,
3190, 3210, 3220, 3240, 1130320, AP5SB, BS-12, FM-15, FS-
12, GS-15, HT-25, JS-12, RM-5H, RR-5, TL-15, WS-12, All DT,
GL, CO and HL series

CHEMICAL NAME:
PRODUCT USE:
MANUFACTURER'S NAME:
ADDRESS:

Hot Melt Glue
Hot Melt Adhesive
FPC Corporation
355 Hollow Hill Drive
Wauconda, IL 60084
847-487-4583
847-487-0174
September 19, 2017

BUSINESS PHONE:
FAX NUMBER:
DATE OF PREPARATION:

2. HAZARD IDENTIFICATION

EMERGENCY OVERVIEW:

Product Description: This product is a solid in various colors, with no odor.
Health Hazards: This product as supplied is classified as an Article and is not expected to cause adverse health effects.
Flammability Hazards: This product is combustible above flash point >450°F (>232°C) if exposed to ignition source.
Reactivity Hazards: None known.
Environmental Hazards: This material is not expected to be an environmental hazard
Emergency Considerations: Emergency responders must wear the proper personal protective equipment (and have appropriate fire-suppression equipment) suitable for the situation to which they are responding.

US DOT SYMBOLS

CANADA (WHMIS) SYMBOLS

EUROPEAN and (GHS) Hazard Symbols

Non-Regulated Material

Not Controlled

None
Signal Word: **None**

This product as supplied does not meet the definition of a hazard class, as defined by HAZCOM 2012 / 29CFR 1910.1200 and the European Union Council Directives 67/548/EEC and subsequent Directives in 76/768/EEC. This product is being evaluated as an Article.

This product as supplied is classified as an "article" according to Title 29 of the Code of Federal Regulations, OSHA Part 1910.1200.

"Article means a manufactured item other than a fluid or particle, which is formed to a specific shape or design during manufacture which has end use function dependent in whole or in part upon its shape or design during end use, and which under normal conditions of use does not release more than very small quantities or trace amounts of a hazardous chemical, and does not pose a physical hazard or health risk to employees."

This product as supplied is odorless, stable, and poses no immediate hazard to health.

GHS LABELING AND CLASSIFICATION:

Classification of the substance or mixture according to OSHA HCS 2012 / 29 CFR 1910. 1200 and Regulation (EC) No 1272/2008, EU No 2015/830 (Amended 1907/2006) and EU 2016/1688

CAS# 24937-78-8 is not listed in ESIS

CAS# 69430-35-9 is not listed in ESIS

EC# 232-479-9 This substance is not classified in the Annex VI

CAS# 68441-37-2 is not listed in ESIS

CAS# 9002-88-4 is not listed in ESIS

COMPONENT(S) DETERMINING HAZARD:

All Ingredients

SAFETY DATA SHEET

GHS Hazard Classification(s):

Not Classified

Hazard Statement(s):

None applicable

Precautionary Statement(s):

None applicable

HEALTH HAZARDS OR RISKS FROM EXPOSURE:

ACUTE: This product as supplied is not expected to cause adverse health effects when used as intended. Ingestion of this product is not a likely route of entry. May cause gastrointestinal irritation if swallowed. Not expected to cause respiratory irritation.

CHRONIC: None known

TARGET ORGANS:

ACUTE: None known

CHRONIC: None known

3. COMPOSITION and INFORMATION ON INGREDIENTS

Hazardous Ingredients:	CAS #	EINECS #	ICSC #	WT %	GHS CLASSIFICATION(S)
Ethylene Vinyl Copolymer	24937-78-8	Not Listed in ESIS	Not Listed	55 - 75%	Not Classified
Resin	69430-35-9	Not Listed in ESIS	Not Listed	0 - 45%	Not Classified
Resin acids and Rosin acids, esters with pentaerythritol	8050-26-8	232-479-9	Not Listed	0 - 45%	Not Classified
Hydrocarbon resin	68441-37-2	Not Listed in ESIS	Not Listed	0 - 45%	Not Classified
Polyethylene Wax	9002-88-4	Not Listed in ESIS	Not Listed	0 - 10%	Not Classified
Balance of other components. Each of the other components is present in less than 1 percent concentration (0.1% concentration for potential carcinogens, reproductive toxins, respiratory tract sensitizers, and mutagens)					

NOTE: This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the CPR, EU Directives and the Japanese Industrial Standard *JIS Z 7250: 2000*. This material is classified as non-hazardous under OSHA regulations 29 CFR 1910.1200.

4. FIRST-AID MEASURES

Contaminated individuals of chemical exposure must be taken for medical attention if any adverse effect occurs. Rescuers should be taken for medical attention, if necessary. Take copy of label and MSDS to health professional with contaminated individual.

SKIN CONTACT: Exposure to non-molten product is not expected to cause adverse effects. Wash hands after handling. If hot molten product contacts skin, cool under running water. Do not remove solidified product. The contaminated individual should seek medical attention.

EYE CONTACT: Exposure to non-molten product is not expected to cause adverse effects. If hot product enters the eyes, flush with water for at least 15 minutes. Contaminated individual should seek medical attention immediately.

INHALATION: If breathing becomes difficult remove contaminated individual to fresh air. Seek medical attention if breathing difficulties continues.

INGESTION: Routine use of this product is not expected to cause any situation which could lead to ingestion. If this product is swallowed, CALL PHYSICIAN OR POISON CONTROL CENTER FOR MOST CURRENT INFORMATION. If professional advice is not available, do not induce vomiting. Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or unable to swallow.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None known.

RECOMMENDATIONS TO PHYSICIANS: Treat symptoms and eliminate overexposure.

SAFETY DATA SHEET

5. FIRE-FIGHTING MEASURES

FLASH POINT: >450°F (>232°C)

AUTOIGNITION TEMPERATURE: Not Established

FLAMMABLE LIMITS (in air by volume, %): Lower NA Upper NA

FIRE EXTINGUISHING MATERIALS: Use fire extinguishing materials appropriate for surrounding fire including water spray (for cooling), dry extinguishing media, carbon dioxide, foam. A solid stream of water may scatter molten product.


UNUSUAL FIRE AND EXPLOSION HAZARDS: This product has no unusual fire or explosion hazards. Do not use water on molten adhesive to avoid splattering and spreading the fire.

Explosion Sensitivity to Mechanical Impact: Not Sensitive

Explosion Sensitivity to Static Discharge: Not Sensitive

SPECIAL FIRE-FIGHTING PROCEDURES: Incipient fire responders should wear eye protection. Structural firefighters must wear Self-Contained Breathing Apparatus and full protective equipment. Isolate materials not yet involved in the fire and protect personnel. Move containers from fire area if this can be done without risk; otherwise, cool with carefully applied water spray. If possible, prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive areas.

NFPA RATING



Hazard Scale: 0 = Minimal 1 = Slight
2 = Moderate
3 = Serious 4 = Severe

6. ACCIDENTAL RELEASE MEASURES

SPILL AND LEAK RESPONSE: Collect and contain for salvage or disposal.

DISPOSAL: Dispose of in accordance with applicable Federal, State, and local procedures (see Section 13, Disposal Considerations).

7. HANDLING and STORAGE

WORK PRACTICES AND HYGIENE PRACTICES: Use good hygiene practices.

STORAGE AND HANDLING PRACTICES: Store in a cool dry location. Protect from physical damage.

8. EXPOSURE CONTROLS - PERSONAL PROTECTION

VENTILATION AND ENGINEERING CONTROLS: Use with adequate ventilation to ensure exposure levels are maintained below the limits provided below. Use local exhaust ventilation, and process enclosure if necessary.

EXPOSURE LIMITS/GUIDELINES:

Component Name	CAS#	ACGIH-TLV's	OSHA PEL's	NIOSH- TLV's	Other
Ethylene Vinyl Copolymer	24937-78-8	Not Listed	Not Listed	Not Listed	None
Resin	69430-35-9	Not Listed	Not Listed	Not Listed	None
Resin acids and Rosin acids, esters with pentaerythritol	8050-26-8	Not Listed	Not Listed	Not Listed	None
Hydrocarbon resin	68441-37-2	Not Listed	Not Listed	Not Listed	None
Polyethylene Wax	9002-88-4	Not Listed	Not Listed	Not Listed	None

Currently, International exposure limits are established for the components of this product. Please check with competent authority in each country for the most recent limits in place.

The following information on appropriate Personal Protective Equipment is provided to assist employers in complying with OSHA regulations found in 29 CFR Subpart I (beginning at 1910.132) or equivalent standard of Canada, or standards of EU member states (including EN 149 for respiratory PPE, and EN 166 for face/eye protection), and those of Japan. Please reference applicable regulations and standards for relevant details.

SAFETY DATA SHEET

RESPIRATORY PROTECTION: Not required for product as supplied. When thermal processing fumes are generated and ventilation is not sufficient to effectively remove them appropriate approved respiratory protection must be provided. Heated product will emit vapors and exposed workers may need to use a NIOSH approved, organic vapor canister type respirator. If necessary, use only respiratory protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29 CFR 1910.134), equivalent U.S. State standards, Canadian CSA Standard Z94.4-93, the European Standard EN149, or EU member states. Oxygen levels below 19.5% are considered IDLH by OSHA. In such atmospheres, use of a full-facepiece pressure/demand SCBA or a full facepiece, supplied air respirator with auxiliary self-contained air supply is required under U.S. Federal OSHA's Respiratory Protection Standard (1910.134-1998) or the regulations of various U.S. States, Canada, EU Member States, or those of Japan. Air-purifying respirators with dust/mist/fume filters are recommended if operations may produce mists or sprays from this product.

EYE PROTECTION: Not required for product as supplied. Wear chemical goggles, face shield if handling molten material. If necessary, refer to U.S. OSHA 29 CFR 1910.133, Canadian Standards, and the European Standard EN166, Australian Standards, or relevant Japanese Standards.

HAND PROTECTION: Not required for product as supplied. Wear thermal insulating gloves to protect from thermal burns. If necessary, refer to U.S. OSHA 29 CFR 1910.138, the European Standard DIN EN 374, the appropriate Standards of Canada, Australian Standards, or relevant Japanese Standards.

BODY PROTECTION: Not required for product as supplied. When thermal processing wear work clothing sufficient to prevent skin contact. If necessary, refer to appropriate Standards of Canada, or appropriate Standards of the EU, Australian Standards, or relevant Japanese Standards.

9. PHYSICAL and CHEMICAL PROPERTIES

SOFTENING POINT: 190°F (88°C)

SPECIFIC GRAVITY @ 20°C: 0.918 – 0.960 (water=1)

VAPOR PRESSURE, mm Hg @ 20°C (68°F): NA

ODOR THRESHOLD: No odor

APPEARANCE, ODOR and COLOR: This product is a solid in various colors, with no odor.

EVAPORATION RATE (n-BuAc=1): Not Applicable

SOLUBILITY IN WATER: Non soluble

pH: NA

10. STABILITY and REACTIVITY

STABILITY: Stable.

DECOMPOSITION PRODUCTS: Thermal degradation produces carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

MATERIALS WITH WHICH SUBSTANCE IS INCOMPATIBLE: The product may react to strong acids, bases and oxidizing agents.

POSSIBILITY OF HAZARDOUS REACTIONS: Will not occur.

CONDITIONS TO AVOID: Avoid excessive overheating. Do not add water or other volatile material to molten adhesive.

11. TOXICOLOGICAL INFORMATION

TOXICITY DATA:

No LD50 Data Available for this product.

Acute toxicity	Based on available data, the classification criteria are not met
Skin corrosion / irritation	Based on available data, the classification criteria are not met
Serious eye damage / irritation	Based on available data, the classification criteria are not met
Respiratory or skin sensitization	Based on available data, the classification criteria are not met
Germ cell mutagenicity	Based on available data, the classification criteria are not met
Carcinogenicity	Based on available data, the classification criteria are not met
Reproductive toxicity	Based on available data, the classification criteria are not met
STOT-single exposure	Based on available data, the classification criteria are not met
STOT-repeated exposure	Based on available data, the classification criteria are not met
Aspiration hazard	Based on available data, the classification criteria are not met

SUSPECTED CANCER AGENT: The components of this product are not listed by agencies tracking the carcinogenic potential of chemical compounds as follows:

SAFETY DATA SHEET

Carcinogenity

NTP Regulated No
IARC Regulated No
OSHA Regulated No

IRITANCY OF PRODUCT: This product can cause skin and eye irritation.

SENSITIZATION TO THE PRODUCT: These products are not known to cause human skin or respiratory sensitization.

REPRODUCTIVE TOXICITY INFORMATION: Listed below is information concerning the effects of this product and its components on the human reproductive system.

Mutagenicity: The components of this product are not reported to produce mutagenic effects in humans.

Embryotoxicity: The components of this product are not reported to produce embryotoxic effects in humans.

Teratogenicity: The components of this product are not reported to produce teratogenicity effects in humans.

Reproductive Toxicity: The components of this product are not reported to produce reproductive effects in humans.

12. ECOLOGICAL INFORMATION

ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

MOBILITY IN SOIL: These products have not been tested for mobility in soil.

PERSISTENCE/DEGRADABILITY: These products have not been tested for persistence or biodegradability. The components may slowly degrade in the environment and form a variety of organic and inorganic materials; however, no specific information is known.

ENVIRONMENTAL STABILITY: These products have not been tested for environmental stability.

BIOACCUMULATION/ACCUMULATION: These products have not been tested for bio-accumulation potential.

13. DISPOSAL CONSIDERATIONS

PREPARING WASTES FOR DISPOSAL: Waste disposal must be in accordance with appropriate U.S. Federal, State, and local regulations, those of Canada, Australia, EU Member States and Japan.

14. TRANSPORTATION INFORMATION

US DOT, IATA, IMO, ADR:

U.S. DEPARTMENT OF TRANSPORTATION (DOT) SHIPPING REGULATIONS: This product is not classified as dangerous goods, per U.S. DOT regulations, under 49 CFR 172.101. Non-Regulated

TRANSPORT CANADA, TRANSPORTATION OF DANGEROUS GOODS REGULATIONS: These products are not classified as Dangerous Goods, per regulations of Transport Canada.

INTERNATIONAL AIR TRANSPORT ASSOCIATION (IATA): These products are not classified as Dangerous Goods, by rules of IATA:

INTERNATIONAL MARITIME ORGANIZATION (IMO) DESIGNATION: These products are not classified as Dangerous Goods by the International Maritime Organization.

EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY ROAD (ADR): These products are not classified by the United Nations Economic Commission for Europe to be dangerous goods

15. REGULATORY INFORMATION

UNITED STATES REGULATIONS:

U.S. SARA REPORTING REQUIREMENTS: The components of these products are not subject to the reporting requirements of Sections 302, 304, and 313 of Title III of the Superfund Amendments and Reauthorization Act.

U.S. SARA THRESHOLD PLANNING QUANTITY: There are no specific Threshold Planning Quantities for any component of these products. The default Federal MSDS submission and inventory requirement filing threshold of 10,000 lb (4,540 kg) therefore applies, per 40 CFR 370.20.

U.S. CERCLA REPORTABLE QUANTITY (RQ): None.

U.S. TSCA INVENTORY STATUS: The components of these products are listed in the TSCA Inventory.

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65): This product does not contain any component above the 0.1% level which is listed as a California Proposition 65 chemical.

SAFETY DATA SHEET

CANADIAN REGULATIONS:

CANADIAN DSL/NDL INVENTORY STATUS: The components of this product are on the DSL Inventory, or are exempted from listing.

CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA) PRIORITIES SUBSTANCES LISTS: No component of this product is on the CEPA First Priorities Substance Lists.

CANADIAN WHMIS CLASSIFICATION and SYMBOLS: Complies with WHMIS 2015

EUROPEAN ECONOMIC COMMUNITY INFORMATION:

SEE SECTION 2 FOR DETAILS

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59): This product does not contain any chemical on the Candidate List.

EU RoHS 2011/65/EU: This product does not exceed the maximum concentration values (MCVs) in EU Directive 2002/95/EC (Restriction of the Use of Certain Hazardous Substances (RoHS) in Electrical and Electronic Equipment), as amended, and/or the MCVs set under EU Directive 2011/65/EU (RoHS recast), as stated in Annex II to that directive. This which means that each of the homogenous materials within this product does not exceed the following MCVs: (a) 0.1% (by weight) for lead, mercury, hexavalent chromium, polybrominated biphenyls or polybrominated diphenyl ethers; and (b) 0.01% (by weight) for cadmium.

AUSTRALIAN INFORMATION FOR PRODUCT:

AUSTRALIAN INVENTORY OF CHEMICAL SUBSTANCES (AICS) STATUS: The components of this product are listed on the AICS or are exempt.

STANDARD FOR THE UNIFORM SCHEDULING OF DRUGS AND POISONS: Not applicable.

JAPANESE INFORMATION FOR PRODUCT:

JAPANESE MINISTER OF INTERNATIONAL TRADE AND INDUSTRY (MITI) STATUS: The components of this product are not listed as Class I Specified Chemical Substances, Class II Specified Chemical Substances, or Designated Chemical Substances by the Japanese MITI.

INTERNATIONAL CHEMICAL INVENTORIES:

Listing of the components on individual country Chemical Inventories is as follows:

Asia-Pac: Listed or exempt

Australian Inventory of Chemical Substances (AICS): Listed or exempt

Korean Existing Chemicals List (ECL): Listed or exempt

Japanese Existing National Inventory of Chemical Substances (ENCS): Listed or exempt

Philippines Inventory of Chemicals and Chemical Substances (PICCS): Listed or exempt

Swiss Giftliste List of Toxic Substances: Listed or exempt

U.S. TSCA: Listed or exempt

16. OTHER INFORMATION

PREPARED BY: Chris Eigbrett

MSDS to GHS Compliance

DATE OF PRINTING: September 14, 2017

Revision Log: 09/19/2017 - Added clarification regarding HCS 2012 compliance and updated template for EU compliance.

Although the information set forth herein is presented in good faith and believed to be correct as of the date of issuance, it has been furnished by our suppliers; consequently, FPC Corporation makes no representations or warranties, express or implied, with respect to information herein presented. The information set forth herein is supplied upon the condition that the persons receiving same will make their own determination as to suitability for their purposes prior to use and relates only to the specific product described and not to such product in combination with any other product. In no event will International Cellulose Corporation be responsible for damages of any nature resulting from the use of or reliance upon this information.

End of SDS Sheet

Safety Data Sheet



1. Identification

Product Name:	WDCARE QT 4PK WATCO DAN OIL NATURAL	Revision Date:	6/17/2016
Product Identifier:	A65741	Supercedes Date:	2/9/2016
Product Use/Class:	Stain/Solvenborne		
Supplier:	Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, IL 60061 USA	Manufacturer:	Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, IL 60061 USA
Preparer:	Regulatory Department		
Emergency Telephone:	24 Hour Hotline: 847-367-7700		

2. Hazard Identification

Classification

Symbol(s) of Product



Signal Word

Danger

Possible Hazards

66% of the mixture consists of ingredient(s) of unknown acute toxicity.

GHS HAZARD STATEMENTS

Flammable Liquid, category 3	H226	Flammable liquid and vapor.
Germ Cell Mutagenicity, category 1B	H340	May cause genetic defects.
Carcinogenicity, category 1B	H350	May cause cancer.
STOT, repeated exposure, category 1	H372	Causes damage to organs through prolonged or repeated exposure.
Eye Irritation, category 2	H319	Causes serious eye irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.

GHS LABEL PRECAUTIONARY STATEMENTS

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. NO SMOKING.
P235	Keep cool.
P201	Obtain special instructions before use.
P281	Use personal protective equipment as required.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P260	Do not breathe dust, fumes, gases, mists, vapors, or spray.
P314	Get medical advice/attention if you feel unwell.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313	If eye irritation persists: Get medical advice/attention.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.

GHS SDS PRECAUTIONARY STATEMENTS

P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P270	Do not eat, drink or smoke when using this product.
P363	Wash contaminated clothing before reuse.

3. Composition/Information On Ingredients**HAZARDOUS SUBSTANCES**

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt.% Range</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
Stoddard Solvent	8052-41-3	50-75	GHS08	H304-372
Rosin Adduct Ester	PROPRIETARY	10-25	GHS07	H317-319
Solvent Naphtha, Light Aromatic	64742-95-6	1.0-2.5	GHS07-GHS08	H304-332-340-350

4. First-aid Measures

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

FIRST AID - SKIN CONTACT: Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

FIRST AID - INGESTION: If swallowed, get medical attention.

5. Fire-fighting Measures

EXTINGUISHING MEDIA: Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS: No unusual fire or explosion hazards noted. Closed containers may explode when exposed to extreme heat due to buildup of steam. Keep containers tightly closed. Combustible liquid and vapor.

SPECIAL FIREFIGHTING PROCEDURES: Evacuate area and fight fire from a safe distance. Use water spray to keep fire-exposed containers cool. Containers may explode when heated.

6. Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers. Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools.

7. Handling and Storage

HANDLING: Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all MSDS/label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

STORAGE: Store in a dry, well ventilated place. Keep container tightly closed when not in use. Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Do not store above 120 ° F. Store large quantities in buildings designed and protected for storage of NFPA Class II combustible liquids. Avoid excess heat.

8. Exposure Controls/Personal Protection

Chemical Name	CAS-No.	Weight % Less Than	ACGIH TLV- TWA	ACGIH TLV- STEL	OSHA PEL-TWA	OSHA PEL- CEILING
Stoddard Solvent	8052-41-3	60.0	100 ppm	N.E.	500 ppm	N.E.
Rosin Adduct Ester	PROPRIETARY	15.0	N.E.	N.E.	N.E.	N.E.
Solvent Naphtha, Light Aromatic	64742-95-6	5.0	N.E.	N.E.	N.E.	N.E.

PERSONAL PROTECTION

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

RESPIRATORY PROTECTION: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

SKIN PROTECTION: Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE EQUIPMENT: Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

HYGIENIC PRACTICES: Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

9. Physical and Chemical Properties

Appearance:	Liquid	Physical State:	Liquid
Odor:	Solvent Like	Odor Threshold:	N.E.
Relative Density:	0.846	pH:	N.A.
Freeze Point, °C:	N.D.	Viscosity:	N.D.
Solubility in Water:	None	Partition Coefficient, n- octanol/water:	N.D.
Decomposition Temp., °C:	N.D.	Explosive Limits, vol%:	1.0 - 7.0
Boiling Range, °C:	-18 - 316	Flash Point, °C:	41
Flammability:	Supports Combustion	Auto-ignition Temp., °C:	N.D.
Evaporation Rate:	Slower than Ether	Vapor Pressure:	N.D.
Vapor Density:	Heavier than Air		

(See "Other information" Section for abbreviation legend)

10. Stability and Reactivity

CONDITIONS TO AVOID: Avoid temperatures above 120°F (49°C). Avoid contact with strong acid and strong bases.

INCOMPATIBILITY: Incompatible with strong oxidizing agents, strong acids and strong alkalis.

HAZARDOUS DECOMPOSITION: When heated to decomposition, it emits acrid smoke and irritating fumes. Contains solvents which may form carbon monoxide, carbon dioxide, and formaldehyde.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

11. Toxicological information

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Substance causes moderate eye irritation.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Substance may cause slight skin irritation.

EFFECTS OF OVEREXPOSURE - INHALATION: High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist. High vapor concentrations are irritating to the eyes, nose, throat and lungs. Prolonged or excessive inhalation may cause respiratory tract irritation.

EFFECTS OF OVEREXPOSURE - INGESTION: Irritating to the nose, throat and respiratory tract. Harmful if swallowed.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Reports have associated repeated and prolonged occupational

overexposure to solvents with permanent brain and nervous system damage.

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
64742-95-6	Solvent Naphtha, Light Aromatic	8400 mg/kg Rat	>2000 mg/kg Rabbit	N.I.

N.I. - No Information

12. Ecological Information

ECOLOGICAL INFORMATION: Product is a mixture of listed components.

13. Disposal Information

DISPOSAL INFORMATION: Dispose of material in accordance to local, state, and federal regulations and ordinances. Do not allow to enter waterways, wastewater, soil, storm drains or sewer systems.

14. Transport Information

	<u>Domestic (USDOT)</u>	<u>International (IMDG)</u>	<u>Air (IATA)</u>	<u>TDG (Canada)</u>
UN Number:	N.A.	1263	1263	N.A.
Proper Shipping Name:	Not Regulated	Paint	Paint	Not Regulated
Hazard Class:	N.A.	3	3	N.A.
Packing Group:	N.A.	III	III	N.A.
Limited Quantity:	No	Yes, >5L No	Yes, >5L No	No

15. Regulatory Information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

No TSCA 12(b) components exist in this product.

16. Other Information**HMS RATINGS**

Health: 2* Flammability: 2 Physical Hazard: 0 Personal Protection: X

NFPA RATINGS

Health: 2 Flammability: 2 Instability: 0

VOLATILE ORGANIC COMPOUNDS, g/L: 485

SDS REVISION DATE: 6/17/2016

REASON FOR REVISION: Substance and/or Product Properties Changed in Section(s):
02 - Hazard Identification
03 - Composition/Information on Ingredients
11 - Toxicological Information
Statement(s) Changed

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

Rust-Oleum Corporation believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Rust-Oleum Corporation makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.