

ITW Permatex
Devcon Brand
10 Columbus Blvd.
Hartford, CT 06106 USA
Telephone: 1-87-Permatex
(877) 376-2839
Emergency: 800-255-3924 (ChemTel)
International Emergency: +01-813-248-0585

567222

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: DUCO PLASTIC & MODEL CEMENT
Product Type: Adhesive

This product appears in the following stock number(s):
90225

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH; TLV-TWA	OSHA PEL
ETHYL ACETATE 141-78-6	>60	400 ppm	400 ppm; 1400 mg/m ³

3. HAZARDS IDENTIFICATION

Toxicity: This material is irritating to skin, eyes and respiratory tract. Ethyl acetate may cause anemia. Prolonged exposure may cause liver and kidney effects and may affect the central nervous system.

Primary Routes of Entry: Eye and skin contact, ingestion, inhalation

Signs and Symptoms of Exposure: May cause pain, redness or swelling of the eyes and excessive blinking and tear production. Ingestion may cause nausea and vomiting. Repeated exposure may cause skin dryness or cracking. Excessive accidental exposure may cause headache, dizziness, nausea and mild respiratory irritation.

Aggravated Medical Condition: Preexisting eye, skin and respiratory disorders may be aggravated by overexposure to this product.

4. FIRST AID MEASURES

Ingestion: Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person

Inhalation: Move to fresh air in case of accidental inhalation of vapours. If symptoms persist, call a physician.

Skin Contact: Remove contaminated clothing and launder before reuse. Wash with soap and water. If skin irritation persists, call a physician.

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists

5. FIRE FIGHTING MEASURES

Flash Point °F(C°): 24°F (4.4°C)

Recommended Extinguishing Media: Carbon dioxide, Dry chemical, Foam

Special Fire-Fighting Procedures: Firefighters should wear self-contained breathing apparatus and protective clothing to prevent all skin and eye contact

Hazardous Products of Combustion: Oxides of carbon, Oxides of nitrogen

Unusual Fire/Explosion Hazards: Closed containers may rupture or explode when exposed to extreme heat.

Lower Explosive Limit: 2%

Upper Explosive Limit: 10.7%

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Eliminate all sources of ignition. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

7. HANDLING AND STORAGE

Storage: Store in a dry area below 90 degrees F. Keep container closed when not in use.

Handling: Warning: Flammable. Do not use near heat, sparks or open flame. Avoid contact with skin and eyes. Use in a well ventilated area. Wash hands before eating and smoking.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes:	Safety glasses
Skin:	Neoprene or nitrile gloves recommended
Ventilation:	General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product
Respiratory Protection:	An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Clear liquid
Odor:	Solvent
Boiling Point:	176°F/80°C
pH:	Not applicable
Solubility in Water:	Slight
Specific Gravity:	0.94
Vapor Pressure:	Not Determined
Vapor Density (Air=1):	>1
Evaporation Rate:	<1 (butyl acetate = 1)

10. STABILITY AND REACTIVITY

Chemical Stability:	Stable at normal conditions
Hazardous Polymerization:	Will not occur
Incompatibilities:	Strong oxidizers, Strong bases, Amines
Conditions to Avoid:	Keep away from heat, sparks and open flame. - No smoking.
Hazardous Products of Combustion:	Oxides of carbon, Oxides of nitrogen

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal:	Disposal should be made in accordance with federal, state and local regulations
US EPA Waste Number:	D001 as per 40CFR 261.21

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

U.S. Department of Transportation - DOT - 49 CFR (Ground)

DOT Shipping Name:	Adhesives, Limited Quantity
Hazard Class:	Class 3, PG II
UN/ID Number:	UN 1133

IATA (Air)

Proper Shipping Name:	Consumer Commodity
Class or Division:	Class 9
UN/ID Number:	ID 8000

IMDG (Vessel)

Proper Shipping Name:	Adhesives, Limited Quantity
Hazard Class:	Class 3, PG II
UN Number:	UN 1133

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

None

California Proposition 65: WARNING: This product contains a chemical known to the State of California to cause cancer.

TSCA Inventory Status: All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 2, FLAMMABILITY 3, REACTIVITY 0

Estimated HMIS Classification: HEALTH 2, FLAMMABILITY 3, PHYSICAL HAZARD 0

(NFPA is a registered trademark of the National Fire Protection Association)

(HMIS is a registered trademark of the National Paint and Coatings Association)

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety

Company: ITW Permatex 10 Columbus Blvd. Hartford, CT USA 06106

Telephone No.: 1-87-Permatex (877) 376-2839

Revision Date: September 25, 2012

Revision Number: 1